

# Demand Specification

## General information

Customer	
Segment	
Project	

### Delivery time

1:st delivery	
Project duration	
Other*	

### Quantity

Total quantity	
Other*	

### Quantity per batch

One Batch	
Qty/batch	
Other*	

### Sealing demands

No demands	
IP 54	
IP 55	
IP 65	
IP 66/67	
IP 68 (specify level)	
0.1 Bar WP	
0.5 Bar WP	
1 Bar WP	
2 Bar WP	
4 Bar WP	
Constant pressure	
Gas pressure	
Blast load	
Exposed temp > 80C	
Retention demands	
Other*	

### Environment

Indoor	
Outdoor	
Offshore	
Ground	
Cabinet	
Shelter	
Other*	

### Frame Material

Mild Steel	
Galvanized steel	
Stainless steel	
Aluminum	
Plastic	
Other*	

### Type of mounting

Bolting	
Casting	
Welding	
Other*	

### Surface treatment

Primed	
Natural anodized	
Chem. Nickel plated	
Powder coated	
Color code	
Untreated	
Other*	

### Wall structure material

Steel	
Aluminum	
Concrete	
Gypsum	
Brick	
Sandwich	
Wall Thickness	
Other*	

### Fire

No Demands	
Civil Construction	
Marine	
Offshore	
One side	
Double side	
Time	
Temp. demand	
Other*	

### EMC

ES	
ES B	
PE	
PE B	
Gasket	
Earthbolt	
Other*	

### Other\* information Cable size/quantity etc



**THORNE &  
DERRICK  
INTERNATIONAL**

**Thorne & Derrick**  
+44 (0) 191 410 4292  
www.powerandcables.com